

ABB TU831V1

3BSE013235R1 | ABB | TU831V1 Extended MTU, 250V

The TU831V1 MTU can have up to 8 I/O channels. The maximum rated voltage is 250 V and maximum rated current is 3 A per channel.

The MTU distributes the ModuleBus to the I/O module and to the next MTU. It also generates the correct address to the I/O module by shifting the outgoing position signals to the next MTU. The MTU can be mounted on a standard DIN rail. It has a mechanical latch that locks the MTU to the DIN rail.

Features and benefits

Greater connection area for larger wires.

Up to 8 isolated channels of field signals.

Connections to ModuleBus and I/O modules.

Mechanical keying prevents insertion of the wrong I/O module.

Latching device to DIN rail for grounding.

DIN rail mounting.

General info

Article number 3BSE013235R1

Type Extended

Connection Terminal block

Channels 8

Voltage 250 V

Mounting Both directions

Mounting detail 55 °C (131 ° F)

Use with I/O DI820, DI821, DO820, and DO821

Process connections 16

up to 8 I/O channels

(2 terminals per channel)

Single/redundant I/O Single

Detailed data

Maximum current per I/O channel 3 A

Acceptable wire sizes Solid: 0.2 - 6mm²

Stranded: 0.2 - 4 mm², 24 - 10 AWG

Recommended torque: 0.5 - 0.6 Nm

Stripping length: 7 mm

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Dielectric test voltage 2000 V a.c.

Environment and certification

CE mark Yes

Electrical safety EN 61010-1, UL 61010-1, EN 61010-2-201, UL 61010-2-201

Hazardous Location -

Marine certification ABS, BV, DNV-GL, LR

Temperature, Operating 0 to +55 ° C (+32 to +131 ° F), approvals are issued for +5 to +55 ° C

Temperature, Storage -40 to +70 ° C (-40 to +158 ° F)

Pollution degree Degree 2, IEC 60664-1

Corrosion protection ISA-S71.04: G3

Relative humidity 5 to 95 %, non-condensing

Max ambient temperature 55 ° C (131 ° F)

Protection class IP20 according to IEC 60529

Mechanical operating conditions IEC/EN 61131-2

EMC EN 61000-6-4, EN 61000-6-2

Overvoltage categories IEC/EN 60664-1, EN 50178

Equipment class Class I according to IEC 61140; (earth protected)

RoHS compliance EN 50581:2012

WEEE compliance DIRECTIVE/2012/19/EU

Dimensions

Width 126 mm (5 in.) including connector,

120.5 mm (4.74 in.) edge to edge installed

Depth 64 mm (2.52 in.) including terminals

Height 110 mm (4.3 in.)

Weight 0.22 kg (0.48 lbs)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com