

ABB TU836V1

The TU836V1 MTU can have up to 8 I/O channels. The maximum rated voltage is 250 V and maximum rated current is 3 A per channel. The MTU distributes the ModuleBus to the I/O module and to the next MTU. It also generates the correct address to the I/O module by shifting the outgoing position signals to the next MTU.

The MTU can be mounted on a standard DIN rail. It has a mechanical latch that locks the MTU to the DIN rail.

Two mechanical keys are used to configure the MTU for different types of I/O modules. This is only a mechanical configuration and it does not affect the functionality of the MTU or the I/O module. Each key has six positions, which gives a total number of 36 different configurations.

Features and benefits

Two groups with 4 channels of field signals and process power connections.

Each channel has one fused load power terminal and one signal return connection.

Process voltage can be connected to 2 individually isolated groups.

Connections to ModuleBus and I/O modules.

Mechanical keying prevents insertion of the wrong I/O module.

Latching device to DIN rail for grounding.

DIN rail mounting.

General info

Article number 3BSE013237R1

Type Extended

Connection Terminal block

Channels 8

Voltage 250 V

Mounting Both directions

Mounting detail 55 °C (131 ° F)

Use with I/O DO820, and DO821

Process connections 16

up to 8 I/O channels

(2 terminals per channel)

4 Process power

4 Process power (0V)

Single/redundant I/O Single

Detailed data

Maximum current per I/O channel 3 A

Maximum current process connection 10 A

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Acceptable wire sizes Solid: 0.2 - 4 mm²
Stranded: 0.2 - 2.5 mm², 24 - 12 AWG
Recommended torque: 0.5 - 0.6 Nm
Stripping length: 7 mm
Dielectric test voltage 2000 V a.c.
Environment and certification
CE mark Yes
Electrical safety EN 61010-1, UL 61010-1, EN 61010-2-201, UL 61010-2-201
Hazardous Location -
Marine certification ABS, BV, DNV-GL, LR
Temperature, Operating 0 to +55 ° C (+32 to +131 ° F), approvals are issued for +5 to +55 ° C
Temperature, Storage -40 to +70 ° C (-40 to +158 ° F)
Pollution degree Degree 2, IEC 60664-1
Corrosion protection ISA-S71.04: G3
Relative humidity 5 to 95 %, non-condensing
Max ambient temperature 55 ° C (131 ° F)
Protection class IP20 according to IEC 60529
Mechanical operating conditions IEC/EN 61131-2
EMC EN 61000-6-4, EN 61000-6-2
Overvoltage categories IEC/EN 60664-1, EN 50178
Equipment class Class I according to IEC 61140; (earth protected)
RoHS compliance EN 50581:2012
WEEE compliance DIRECTIVE/2012/19/EU
Dimensions
Width 126 mm (5 in.) including connector, 120.5 mm (4.74 in.) edge to edge installed
Depth 64 mm (2.52 in.) including terminals
Height 110 mm (4.3 in.)
Weight 0.26 kg (0.57 lbs)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com