

# MITSUBISHI HG-MR053B

The Mitsubishi HG-MR053B servo motor features ultra-low inertia, making it ideal for applications requiring rapid response. With a rated output of 0.05 kW and a maximum speed of 6000 r/min, this motor performs smaller tasks efficiently.

Technical specifications for HG-MR053B

Manufacturer Mitsubishi

Product Line HG Series

Part Number HG-MR053B

Weight 10.00 lbs (4.54 kg)

Product Servo Motor

Inertia Ultra-Low Inertia

Capacity Small Capacity

Rated Output 0.05 kW

Rated Speed 3000 r/min

Electromagnetic Brake Built-In Electromagnetic Brake

Oil Seal None

Maximum Speed 6000 r/min

Shaft Shape Standard

Rated Torque 0.16 Nm

Maximum Torque 0.48 Nm

Rated Current 1A

Maximum Current 3.1A

Description

The Mitsubishi HG-MR053B is a compact servo motor engineered for precision applications. With an ultra-low inertia characteristic, this motor quickly adapts to dynamic changes in speed and torque, ensuring optimal performance in controlled environments. Operating efficiently at a rated output of 0.05 kW, the unit provides reliability in tasks with lower power characteristics.

At a rated speed of 3000 r/min, the HG-MR053B can reach a peak speed of 6000 r/min, offering flexibility in various operational scenarios. The motor generates a rated torque of 0.16 Nm and supports a maximum torque of 0.48 Nm, making it suitable for small-capacity tasks.

The integrated electromagnetic brake also contributes to enhanced operational precision, allowing for exact control during movement. However, it's important to note that the HG-MR053B does not include an oil seal, which may affect its suitability in specific environments. The standard shaft design facilitates ease of integration with existing machinery setups.

You can contact us through the following contact information

[www.sparetechplc.com](http://www.sparetechplc.com) +86 180 3000 5825 [sales@sparetechplc.com](mailto:sales@sparetechplc.com)

Current specifications indicate a rated current requirement of 1A, which can handle up to 3.1A at peak. This makes the Mitsubishi HG-MR053B an efficient solution for applications requiring quick responsiveness and controlled operation.



You can contact us through the following contact information

[www.sparetechplc.com](http://www.sparetechplc.com) +86 180 3000 5825 [sales@sparetechplc.com](mailto:sales@sparetechplc.com)