

Allen-Bradley 1794-OB8EP

The Allen-Bradley 1794-OB8EP Flex I/O Digital DC Output Module has 8 Sourcing Current Outputs, a 24V DC On-state Voltage nom., and a 2A max. per Output Output Current Rating. It also operates with a 0.2V DC On-state Voltage Drop max. and a 0.5mA Off-state Leakage Current max..

Technical specifications for 1794-OB8EP

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1794-OB8EP

Product Type Flex I/O Digital DC Output Module

Outputs 8 Sourcing Current

On-state Voltage nom. 24V DC

Output Current Rating 2A max. per Output

On-state Current max. 2A per Channel

On-state Voltage Drop max. 0.2V DC

Off-state Leakage Current max. 0.5mA

Isolation Voltage 50V Continuous

Flexbus Current 73mA @ 5V DC

Power Dissipation 5.5W @ 31.2V DC max.

Thermal Dissipation 18.8 BTU/hr. @ 31.2V DC max.

UPC 10612598172648 Description

The Allen-Bradley 1794-OB8EP is a 1794 FLEX Digital DC Output Module. It is an Electronic Fuse (EP) module which acts to disconnect the output if a fault occurs. The 1794-OB8EP is fitted inside the terminal bus, making a connection with the field devices and the I/O bus. Modules can be inserted or removed under power since the I/O module does not have any direct wiring. It in turn saves time and removes system restarting inefficiency. The 1794-OB8EP module has 8 current sourcing outputs. It has 24V DC nominal On-State output voltage, 19.2 – 31.2V DC On-State output voltage, and 2A per channel with 10A per module maximum On-State output current. It has a maximum output delay time of 0.1ms from Off-to-On and vice versa. It has a maximum power dissipation of 5.5W at 31.2V DC. Terminal Base units compatible with it are the 1794-TB2, 1794-TB3, 1794-TB3S, 1794-TBN, and the 1794-TBKD. The 1794-OB8EP has an external power supply of 19.2 - 31.2V DC voltage with a 5% AC ripple and 20 - 35mA current. It is installed using a DIN rail by simply snapping it onto the DIN rail. It has various communication options such as ControlNet, DeviceNet, EtherNet/IP, and Universal Remote I/O. The 1794-OB8EP module has 16 yellow LED status indicators for each channel corresponding input device and output signal. It also has XT versions of standard modules for operating in extreme environments. This reduces panel and maintenance costs.

Revisions

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com