

Bently Nevada 330708-00-10-90-11-05

"Manufacturer : Bently Nevada

Product No. :330708-00-10-90-11-05

Product type : 3300 XL 11 mm Proximity Probes

Made in U.S.A

330708 = 3300 XL 11 mm Probe, 5/8-18 UNF thread, without armor

Unthreaded Length Option : 00=0 in

Overall Case Length Option :10= 1.0 in

Total Length Option :90 = 9.0 meters (29.5 feet)

Connector and Cable-Type Option : 11

Miniature coaxial ClickLoc

connector with connector

protector, FluidLoc cable

Agency Approval Option :05 Multiple Approvals

Probe Tip Material: Polyphenylene sulfide (PPS).

Probe Case Material: AISI 304 stainless steel (SST).

Probe Cable Specifications: 75 Ω triaxial, fluoroethylene propylene (FEP) insulated probe cable in the following total probe lengths: 1, 5 or 9 metres.

Operating and Storage Temperature: -51° C to +177° C (-60° F to +351° F)

Probe Pressure: 3300 XL probes are designed to seal differential pressure between the probe tip and case. The probe sealing material consists of a Viton* O-ring. Probes are not pressure tested prior to shipment. Contact our custom design department if you require a test of the pressure seal for your application

Shipping weight : 0.17 Kg

Probe dc Resistance

Probe

Length (m) 9.0

Resistance from the Center

Conductor to the Outer

Conductor (RPROBE) (ohms) 8.5 $\pm$ 1.1

Probe Case Thread 5/8-18

Maximum Length of Thread Engagement 0.938 in

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Probe Case Torque 1/2-20 and 5/8-
18 probe cases
Maximum Rated 45.2 N•m (400 in•lb)
Recommended
15.2 N•m
(133 in•lb)

Probe Tip
Material Polyphenylene sulfide (PPS).
Probe Case
Material AISI 304 stainless steel (SST).
Probe Cable
Specification
75 Ω triaxial, fluoroethylene
propylene (FEP) insulated
probe cable in the following
total probe lengths: 1, 5 or 9
meters.

Connector-to-connector torque
Recommended
torque Finger tight
Maximum
torque 0.565 N•m (5 in•lb)
Minimum Bend
Radius (with or
without SST
armor)
25.4 mm (1.0 in)

Probe Case Thread M16x1.5
Maximum Length of Thread Engagement 24 mm

Probe Case Thread M14x1.5
Maximum Length of Thread Engagement 21 mm

Probe Temperature Range
Operating and
Storage
Temperature
-52° C to +177° C (-62° F to

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

+351° F)

Exposing the probe to temperatures below -34° C (30° F) may cause premature failure of the pressure seal.

|||||



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com