

Scheinder Electric TM221C16T

TM221C16T

controller M221 16 IO transistor PNP

Main

Range of product Modicon M221

Product or component type Logic controller

[Us] rated supply voltage 24 V DC

Discrete input number 9 discrete input conforming to IEC 61131-2 Type 1 including 4 fast input

Analogue input number 2 at input range: 0...10 V

Discrete output type Transistor

Discrete output number 7 transistor including 2 fast output

Discrete output voltage 24 V DC

Discrete output current 0.5 A

Complementary

Discrete I/O number 16

Number of I/O expansion module ≤ 4 for transistor output
 ≤ 4 for relay output

Supply voltage limits 20.4...28.8 V

Inrush current ≤ 35 A

Power consumption in W ≤ 10 W at 24 V with max number of I/O expansion module
 ≤ 3.9 W at 24 V without I/O expansion module

Power supply output current 0.325 A at 5 V for expansion bus

0.15 A at 24 V for expansion bus

Discrete input logic Sink or source (positive/negative)

Discrete input voltage 24 V

Discrete input voltage type DC

Analogue input resolution 10 bits

LSB value 10 mV

Conversion time 1 ms per channel + 1 controller cycle time for analog input

Permitted overload on inputs ± 30 V DC for analog input with 5 min maximum
 ± 13 V DC for analog input permanent

Voltage state 1 guaranteed ≥ 15 V for input

Voltage state 0 guaranteed ≤ 5 V for input

Discrete input current 7 mA for discrete input

5 mA for fast input

Input impedance 4.9 kOhm for fast input

3.4 kOhm for discrete input

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

100 kOhm for analog input
Response time 35 μ s turn-off operation for input; I2...I5 terminal
5 μ s turn-on operation for fast input; I0, I1, I6, I7 terminal
35 μ s turn-on operation for input; other terminals terminal
5 μ s turn-off operation for fast input; I0, I1, I6, I7 terminal
100 μ s turn-off operation for input; other terminals terminal
5 μ s turn-on, turn-off operation for output; Q0...Q1 terminal
50 μ s turn-on, turn-off operation for output; Q2...Q3 terminal
300 μ s turn-on, turn-off operation for output; other terminals terminal
Configurable filtering time 0 ms for input
12 ms for input
3 ms for input
Discrete output logic Positive logic (source)
Current per output common 3.5 A
Output frequency 100 kHz for fast output (PWM/PLS mode) at Q0...Q1 terminal
5 kHz for output at Q2...Q3 terminal
0.1 kHz for output at Q4...Q6 terminal

Absolute accuracy error +/- 1 % of full scale for analog input
Leakage current 0.1 mA for transistor output
Voltage drop $\leq$ 1 V
Mechanical durability $\geq$ 20000000 cycles for transistor output
Tungsten load $\leq$ 12 W for output and fast output
Protection type Overload and short-circuit protection at 0.2 A
Reset time 1 s automatic reset
Memory capacity 256 kB for user application and data RAM with 10000 instructions
256 kB for internal variables RAM
Data backed up 256 kB built-in flash memory for backup of application and data
Data storage equipment 2 GB SD card optional
Battery type BR2032 lithium non-rechargeable, battery life: 4 yr
Backup time 1 year at 25 $^{\circ}$ C by interruption of power supply
Execution time for 1 KInstruction 0.3 ms for event and periodic task
Execution time per instruction 0.2 μ s Boolean
Exct time for event task 60 μ s response time
Maximum size of object areas 512 %M memory bits
8000 %MW memory words
512 %KW constant words
255 %TM timers
255 %C counters
Realtime clock With
Clock drift $\leq$ 30 s/month at 25 $^{\circ}$ C

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Regulation loop Adjustable PID regulator up to 14 simultaneous loops
Positioning functions Position PTO 2 axe(s) pulse/direction mode (100 kHz)
Position PTO 1 axe(s) CW/CCW mode (100 kHz)
Function available PWM
PLS
Frequency generator
Counting input number 4 fast input (HSC mode) (counting frequency: 100 kHz), counting capacity:
32 bits
Control signal type A/B
Pulse/direction
Single phase
Integrated connection type USB port with connector mini B USB 2.0
Non isolated serial link "serial 1" with connector RJ45 and interface RS485
Non isolated serial link "serial 2" with connector RJ45 and interface RS232/RS485
Supply Serial serial link supply at 5 V 200 mA
Transmission rate 1.2...115.2 kbit/s (115.2 kbit/s by default) for bus length of 15 m -
communication
protocol: RS485
1.2...115.2 kbit/s (115.2 kbit/s by default) for bus length of 3 m - communication
protocol: RS232
480 Mbit/s - communication protocol: USB
Communication port protocol USB port : USB protocol - SoMachine-Network
Non isolated serial link : Modbus protocol master/slave - RTU/ASCII or SoMachineNetwork
Local signalling 1 LED red for module error (ERR)
1 LED green for PWR
1 LED green for RUN
1 LED green for SD card access (SD)
1 LED red for BAT
1 LED green for SL1
1 LED green for SL2
1 LED per channel green for I/O state
Electrical connection Mini B USB 2.0 connector for a programming terminal
Terminal block, 3 terminal(s) for connecting the 24 V DC power supply
Connector, 4 terminal(s) for analogue inputs
Removable screw terminal block for inputs
Removable screw terminal block for outputs
Cable distance between devices Shielded cable: 10 m for fast input
Unshielded cable: 30 m for output
Unshielded cable: 30 m for digital input
Unshielded cable: 1 m for analog input
Shielded cable: 3 m for fast output

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Insulation Non-insulated between inputs
Non-insulated between analogue inputs
500 V AC between output and internal logic

500 V AC between input and internal logic
Non-insulated between analogue input and internal logic
1500 V AC between supply and ground
500 V AC between input and ground
2300 V AC between supply and internal logic
Marking CE

Mounting support Top hat type TH35-15 rail conforming to IEC 60715
Top hat type TH35-7.5 rail conforming to IEC 60715
Plate or panel with fixing kit

Height 90 mm

Depth 70 mm

Width 95 mm

Product weight 0.346 kg

Environment

standards EN/IEC 60664-1

EN/IEC 61131-2

EN/IEC 61010-2-201

product certifications ABS

CSA

CULus

LR

IACS E10

RCM

EAC

DNV-GL

environmental characteristic Ordinary and hazardous location

resistance to electrostatic discharge 4 kV on contact conforming to EN/IEC 61000-4-2

8 kV in air conforming to EN/IEC 61000-4-2

resistance to electromagnetic fields 10 V/m (80 MHz...1 GHz) conforming to EN/IEC 61000-4-3

3 V/m (1.4 GHz...2 GHz) conforming to EN/IEC 61000-4-3

1 V/m (2...2.7 GHz) conforming to EN/IEC 61000-4-3

resistance to magnetic fields 30 A/m 50/60 Hz conforming to EN/IEC 61000-4-8

resistance to fast transients 2 kV for power lines conforming to EN/IEC 61000-4-4

2 kV for relay output conforming to EN/IEC 61000-4-4

1 kV for Ethernet line conforming to EN/IEC 61000-4-4

1 kV for serial link conforming to EN/IEC 61000-4-4

1 kV for I/O conforming to EN/IEC 61000-4-4

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

surge withstand 2 kV for power lines (AC) in common mode conforming to EN/IEC 61000-4-5
 2 kV for relay output in common mode conforming to EN/IEC 61000-4-5
 1 kV for I/O in common mode conforming to EN/IEC 61000-4-5
 1 kV for shielded cable in common mode conforming to EN/IEC 61000-4-5
 0.5 kV for power lines (DC) in differential mode conforming to EN/IEC 61000-4-5
 1 kV for power lines (AC) in differential mode conforming to EN/IEC 61000-4-5
 1 kV for relay output in differential mode conforming to EN/IEC 61000-4-5
 0.5 kV for power lines (DC) in common mode conforming to EN/IEC 61000-4-5
 resistance to conducted disturbances 10 Vrms (0.15...80 MHz) conforming to EN/IEC 61000-4-6
 3 Vrms (0.1...80 MHz) conforming to Marine specification (LR, ABS, DNV, GL)
 10 Vrms (spot frequency (2, 3, 4, 6.2, 8.2, 12.6, 16.5, 18.8, 22, 25 MHz)) conforming to
 Marine specification (LR, ABS, DNV, GL)
 electromagnetic emission Conducted emissions conforming to EN/IEC 55011 power lines (AC),
 0.15...0.5 MHz :
 79 dB μ V/m QP/66 dB μ V/m AV
 Conducted emissions conforming to EN/IEC 55011 power lines (AC), 0.5...300 MHz :
 73 dB μ V/m QP/60 dB μ V/m AV
 Conducted emissions conforming to EN/IEC 55011 power lines, 10...150 kHz :
 120...69 dB μ V/m QP
 Conducted emissions conforming to EN/IEC 55011 power lines, 1.5...30 MHz : 63
 dB μ V/m QP
 Radiated emissions conforming to EN/IEC 55011 class A 10 m, 30...230 MHz : 40
 dB μ V/m QP
 Conducted emissions conforming to EN/IEC 55011 power lines, 150...1500 kHz :
 79...63 dB μ V/m QP
 Radiated emissions conforming to EN/IEC 55011 class A 10 m, 200...1000 MHz : 47
 dB μ V/m QP
 immunity to microbreaks 10 ms
 ambient air temperature for operation -10...55 ° C for horizontal installation
 -10...35 ° C for vertical installation
 ambient air temperature for storage -25...70 ° C
 relative humidity 10...95 % without condensation in operation

 10...95 % without condensation in storage
 IP degree of protection IP20 with protective cover in place
 pollution degree $\leq$ 2
 operating altitude 0...2000 m
 storage altitude 0...3000 m
 vibration resistance 3.5 mm (vibration frequency: 5...8.4 Hz) on symmetrical rail
 1 gn (vibration frequency: 8.4...150 Hz) on symmetrical rail
 3.5 mm (vibration frequency: 5...8.4 Hz) on panel mounting

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

1 gn (vibration frequency: 8.4...150 Hz) on panel mounting

shock resistance 147 m/s² (test wave duration:11 ms)

Offer Sustainability

Sustainable offer status Green Premium product

RoHS (date code: YYWW) Compliant - since 1415 - Schneider Electric declaration of conformity

REACH Reference not containing SVHC above the threshold

Product environmental profile Available

Product end of life instructions Available



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com