

Schneider Electric TCSESU053FN0

TCSESU053FN0

Ethernet TCP/IP switch - ConneXium - 5 ports for copper

Main

Range of product ConneXium

Product or component type Ethernet TCP/IP unmanaged switch

Concept Transparent Ready

Communication port protocol Ethernet TCP/IP

Port Ethernet 10BASE-T/100BASE-TX - 5 port(s) copper cable

Maximum number of switches in cascade

Unlimited

Complementary

Integrated connection type Shielded RJ45 copper cable

Transmission support medium Twisted shielded pairs cable CAT 5E for copper cable

Ethernet service Automatic negotiation of 10/100 Mbit/s and duplex mode

Auto MDI/MDX

Automatic change of polarity

Storage and re-routing of received data

[Us] rated supply voltage 24 V

Supply voltage limits 9.6...32 V DC SELV

Power consumption in W 2.2 W

Electrical connection Removable connector 3 ways power supply

Marking CE

Local signalling 1 LED power supply

1 LED per channel copper port activity

1 LED per channel 10 or 100 Mbit/s data rate

Ethernet cabling system TF switches

Width 25 mm

Height 114 mm

Depth 79 mm

Product weight 0.113 kg

Environment

Ambient air temperature for operation 0...60 ° C

Relative humidity > 0...95 % without condensation

IP degree of protection IP30

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Standards CSA C22.2 No 142

CUL 508

Product certifications CE



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com