

Delta VFD4A2MS43ANSAA

Delta VFD4A2MS43ANSAA MS300 Series Drive

Series: MS-300 460 V 3 Phase 2 HP 1.5 KW 0 – 599 Hz IP 20 Optional EMC Filter Heavy Duty
Output: 4.2 A Normal Duty Output: 4.6 A

PRODUCT SPECIFICATIONS

Model Name VFD4A2MS43ANSAA

Series MS-300 Series

Input Voltage – Phase 460 V – 3 Phase

Motor Power Range 2 HP – 1.5 KW

Frequency 0 – 599 Hz

Frame Size B1

IP Level IP 20

EMC Filter Optional

Normal Duty* Amps 4.6 A

Heavy Duty** Amps : 4.2 A

Weight 3 Lbs

Dimensions 2.83 (in) x 5.59 (in) x 5.63 (in)

SERIES DESCRIPTION

The MS300 is Delta's compact vector control drive line.

Optimized Space Utilization

Compact Design | Side-by-Side Installation

Communication Options

Built-in RS-485 (Modbus) and various communication card options: CANopen, PROFIBUS DP, DeviceNet, MODBUS TCP, EtherNet/IP, EtherCAT, PROFINET. Removable 5-digit LED keypad for remote operation

Outstanding Drive Performance

Supports IM and PM Motors | High Starting Torque | Enhanced Braking Capability | Fast Response to Load Impact | Deceleration Energy Backup (DEB)

Strong System Support

Multi-motor Control | Pulse Control | Built-in PLC | Tension Control | DC 24 V External Power | High Overload Capability | Built-in Brake Chopper | Closed-Loop Control

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Wide Range of Applications

Rewinder Machines | Slitter Machines | Printing Machines | Drawing Machines | Coil Winding Machines | Machine Tools | Woodworking Machines | Textile Machines

額定功率: 1.5 kW

額定電流: 4.2 A

階段數目: 3 Phase

IP 額定值: IP20

系列: VFD-MS300

品牌: Delta Electronics

特徵: Support for both IM and PM Motor Control

框架尺寸 - NEMA: Frame B1

機動機驅類型: Variable Frequency Drive

工作電源電壓: 460 V

產品類型: Motor Drives



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com