

GE Fanuc IC697MDL752

The IC697MDL752 module is a GE Fanuc module that has 32 output points. The unit is part of GE Series 90-70 and it has a rated voltage of 12 Volts DC. The output voltage range of the module is 10 to 15 Volts DC and the output currents are 0.5 Amps and 2 Amps per point and per group, respectively.

Technical specifications for IC697MDL752

Brand GE Fanuc

Series Series 90-70

Part Number IC697MDL752

Rated voltage 12 Volts DC

Output current 0.5 Amps per point, 2 Amps per group

Output voltage range 10 to 15 Volts DC

Required current 0.25 Amps

Number of outputs 32

Isolation voltage 1500 Volts

Inrush current 10 Amps (maximum) for 20 milliseconds

Response time-on 1 millisecond (maximum)

Response time-off 1 millisecond (maximum)

Output voltage drop 1 Volt/2 Ohms (maximum)

The IC697MDL752 output module is a GE Fanuc component that is designed for installation into the rack of a GE Series 90-70 PLC. The module provides the possibilities of configuration and customization for various machine systems and applications and it operates on a DC power sources. This high-quality PLC accessory operates as positive logic discrete output module and it offers up to 32 output points. Like other similar components from this series, this output module also has universal features like a special keying system and organized wiring. The module is intended for use with programmable controllers which serve as the essential hardware for large and complex machine systems that operate in harsh industrial conditions.

The IC697MDL752 output module responds in just 1 millisecond when it is turned on and when it is turned off. The highly reliable output module has all the necessary protective features and it meets requirements of the bus standards such as the VME standards. The module follows regulations that are set in the C.1 revision of the standards and it requires 0.25 Amps of current. The IC697MDL752 module has a 12 Volts DC voltage rating and its outputs are separated into 4 groups of 8. The module has a 10 to 15 Volts DC voltage range for outputs and it has 10 Amps of inrush current. The IC697MDL752 module can be installed in just a couple of simple steps. Also, the removal of the module from the rack can be done easily by pressing the plastic clips located on the backside of the housing cover. Additionally, the module features a convenient wiring terminal board that allows for the installation of wires with gauges of AWG #22 or #14.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com