

Schneider Electric 140ESI06210

ASCII serial link module Modicon Quantum - 2 RS232C port

140ESI06210

Main

Range of Product

Modicon Quantum automation platform

Product or Component Type

ASCII serial link module

Software name

Concept > V2

ProWORX 32 > V2

ProWORX NxT > V2

Unity Pro > V2

Complementary

Product Compatibility

All Quantum CPU

Product Specific Application

For standard applications

Mode of Transmission

ASCII

Number of port

2 RS232C non isolated DIN 66020

Electrical connection

2 connectors SUB-D 9

Transmission Rate

19.2 kbit/s

Maximum cable distance between devices

<65.6 ft (20 m)

Message nesting

8 levels

Buffer size

255 I bytes/255 O bytes

Number of messages

255

Message length

127 characters + 1 checksum maximum

Clock

With calendar clock

Memory capacity

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

128 kB flash
32 kB RAM
Maximum power dissipation in W
2 W
Addressing requirement
12 output words
12 input words
Bus current requirement
300 mA
Module format
Standard
Product Weight
0.7 lb(US) (0.3 kg)
Environment
Resistance to electromagnetic fields
9.1 V/m (10 V/m) 80...1000 MHz IEC 801-3
Ambient Air Temperature for Operation
32...140 ° F (0...60 ° C)
Ambient Air Temperature for Storage
-40...185 ° F (-40...85 ° C)
Relative Humidity
95 % without condensation
Operating altitude
≤ 16404.2 ft (5000 m)
Ordering and shipping details
Category
US1PC2118155
Discount Schedule
PC21
GTIN
3595861000155
Returnability
Yes
Packing Units
Unit Type of Package 1
PCE
Nbr. of units in pkg.
1
Package 1 Height
1.97 in (5.0 cm)
Package 1 Width

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

6.50 in (16.5 cm)

Package 1 Length

12.40 in (31.5 cm)

Package weight(Lbs)

14.9 oz (423.0 g)



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com