

Bently Nevada 330500-06-00

Manufacturer : Bently Nevada

Product No. : 330500-06-00

Product Type : Velomitor Piezo-velocity Sensor

Made in U.S.A

Model : 330500 =- Velomitor Piezo-velocity Sensor

Mounting Thread Option : -06= 5/8 - 18 UNF

Agency Approval Option : -00= - Not required

Parameters are specified from +20 ° C to +30 ° C
(+68 ° F to +86 ° F) and at 100 Hz unless otherwise
indicated.

Operating the transducer outside the
specified limits may result in false
readings or loss of machine
monitoring.

Electrical

Sensitivity

3.94mV/mm/s (100 mV/in/s)

±5%.

Frequency

Response

4.5 Hz to 5 kHz (270 cpm to
300 kcpm) ±3.0 dB.

6.0 Hz to 2.5 kHz (360 cpm to
150 kcpm) ±0.9 dB.

Temperature

Sensitivity

-14% to +7.5% typical over the
operating temperature
range.

Velocity Range 1270 mm/s (50 in/s) peak.

Transverse

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Sensitivity

Less than 5% of sensitivity.

Amplitude

Linearity

$\pm 2\%$ to 152 mm/s (6 in/s)

peak.

Mounted

Resonant

Frequency

Greater than 12 kHz.

Output Bias

Voltage

-12 $\pm$ 3.0 VDC, over

temperature referenced to

Pin A.

Dynamic

Output

Impedance

Less than 2400 Ω

Broadband

Noise Floor (4.5

Hz to 5 kHz)

0.004 mm/s (160 μ in/s) rms,
nominal

Grounding Case isolated

Maximum

Cable Length

305 metres (1,000 feet) of
cable, part number 02173006,
with no degradation of
signal.

Environmental Limits

Operating

Temperature

Range

-55° C to 121° C

(-67° F to 250° F)

Shock

Survivability

5,000 g peak, maximum

Relative

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Humidity

To 100% non-submerged;
case is hermetically-sealed.

Base Strain

Sensitivity

0.005 in/s/mstrain.

Magnetic Field

Susceptibility

<51 min/s/gauss (50 gauss,
50-60Hz).

Physical

Weight 142 grams (5.0 oz), typical.

Diameter 25.3 mm (0.995 in).

Height 63.2 mm (2.49 in).

Case Material 316L stainless steel.

Connector

2-pin Mil-C-5015

hermetically-sealed, 316L
stainless steel shell.

Mounting

Torque

32-46 kg cm (24-40 in-lb)
max.

Polarity

When the sensor case
motion is toward the
connector, Pin A becomes
positive with respect to pin B.

Recommended

cable length

(assuming

max vibration

of 50g,

frequency 10

kHz, and cable

capacitance

200 pf/m.)

208 ft (63m)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Compliance and Certifications

FCC

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

I This device may not cause harmful interference.

I This device must accept any interference received, including interference that may cause undesired operation.

EMC

EMC Directive 2014/30/EU

RoHS

RoHS Directive 2011/65/EU

Maritime

DNV rules for classification - Ships

DNV rules for classification - High speed and light craft

DNV offshore standards

Hazardous Area Approvals

330500 Ex ia IIC T4

AEx ia IIC T4

Class I, Division 1, Groups A, B, C and D

Class II, Groups E, F, G

Class III

Install per dwg 167537

T4 @ $-40^{\circ}\text{C} \leq T_a \leq 100^{\circ}\text{C}$

Ex nL IIC T4

AEx nA IIC T4

Class I, Div 2, Groups A, B, C, D

Install per dwg 167537

T4 @ $-40^{\circ}\text{C} \leq T_a \leq 100^{\circ}\text{C}$

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com