

Bently Nevada 330901-14-43-05-02-05

Manufacturer : Bently Nevada

Product Type : 3300 NSv Proximity Probes

Product No :330901-14-43-05-02-05

Product Type : 3300 NSv Proximity Probes

Made in U.S.A

330901 = 3300 NSv Probe, 1/4-28 UNF thread, without armor

Unthreaded Length Option :14 = 1.4 in

Overall Case Length Option :43=4.3 in

Total Length Option : 05 = 0.5 meter (20 in)

Connector and Cable-Type Option :02= Miniature coaxial ClickLoc connector,
standard cable

Agency Approval Option :05= Multiple Approvals

Probe Case Material : AISI304 stainless steel (SST).

Probe Tip Material : Polyphenylene sulfide (PPS).

Probe Cable Specifications: 75 Ω coaxial, fluoroethylene propylene (FEP) insulated probe cable
in the following total probe lengths: 0.5, 1, 5, or 7 metres.

Probe dc Resistance

Probe Length (m) 1.0m

Resistance from the Center

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Conductor to the Outer
Conductor (RPROBE)
(ohms)
4.2 $\pm$ 0.5

Connector-to-connector Torque

Probe Case

Torque

Maximum

Rated Recommended

3/8-24 or

M10X1 probe

cases

33.9 N•m

(300 in•lb)

11.3 N•m

(100 in•lb)

3/8-24 or

M10X1 probe

cases – first

three

threads

22.6 N•m

(200 in•lb)

7.5 N•m

(66 in•lb)

Thread Engagement Limits

Probe

Case

Thread

Maximum Length of Thread

Engagement

3/8-24 0.563 in

Probe Temperature Range

Operating

Temperature

-52° C to +177° C (-62° F to

+351° F)



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Storage

Temperature

-52° C to +177° C (-62° F to +351° F)

Exposing the probe

to temperatures

below -34° C (-30° F)

for a sustained

period of time may

cause premature

failure of the

pressure seal.

Probe

Pressure

3300 NSv probes are designed to seal differential pressure between the probe tip and case. The probe sealing material consists of a Viton O-ring. Probes are not pressure tested prior to shipment.

Probe Approximately 14 to 150 g
(0.5 to 5.3 oz)

Temperature

Classification

Ambient Temperature

(Probe Only)

For EPL Ga and Gc

T1 -55° C to +232° C

T2 -55° C to +177° C

T3 -55° C to +120° C

T4 -55° C to +80° C

T5 -55° C to +40° C

For EPL Dc

T280° C @ Ta -55° C to +232° C

T225° C @ Ta -55° C to +177° C

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

T170° C @ Ta -55C to +120° C
T130° C @ Ta -55° C to +80° C
T105° C @ Ta -55° C to +100° C
T90° C @ Ta -55° C to +40° C



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com