

Bently Nevada 21000-28-05-00-105-04-02

Product Number: 21000-28-05-00-105-04-02
Model: Proximity Probe Housing Assemblies
Manufacturer: Bently Nevada
Condition: New & Original in Factory Packing
Factory Warranty: 12 Months

Ordering Information

Model: 21000 - Proximity Probe Housing Assemblies
Suffix Codes:
Probe Option, with Connector: 28 3300 XL 8 mm probe, selectable
hazardous area approvals
Probe Cable Length 05 0.5 m (20 in)
Standoff Adapter: No standoff adapter = 00

Probe Penetration: 105=10.5 in
Fitting Option: 04 One 3/4-14 NPT plug only

Mounting Thread Option: 02
3/4-14 NPT
Must be ordered if Standoff
Adapter Length option is not
00.

Material

21000 Aluminum body with 304
stainless steel sleeve

Probe Cable Length 0.5 m
Maximum (C) + (D)
with visible probe
(P/N and S/N) Not visible
Maximum (C) + (D) Dimension

13.5 in (34.3 mm)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

1.1 kg (2.4 lb) typical,
without fittings

The 21000 and 24701 Proximity Probe Housing Assemblies consist of the following parts:

- I A dome cover that screws into the body of the housing
- I Threaded ports for conduit connections
- I A probe sleeve of optional length
- I O-rings
- I A reverse mount proximity probe
- I A thread seal
- I Optional conduit fittings
- I An optional standoff adapter

The 21000 and 24701 Proximity Probe Housing Assemblies are available with Canadian Standards Association (CSA) approvals. They are rated explosion proof for hazardous areas.

You can order hazardous area approved proximity probes with 21000 aluminum and 24701 stainless steel housings for intrinsically safe applications. Both housings are certified as CSA Type 4 enclosures and are fully compliant with the American Petroleum Institute's (API) 670 Standard for externally mounted proximity probe housings.

Compliance and Certifications

RoHS

European Community Directive:

RoHS Directive 2011/65/EU

21000 and 24701

CA21000 and CA24701 housings are certified by CSA for explosion-proof applications in the following areas:

North

America

Class I Divisions 1 and 2 Groups C and D

Class II Divisions 1 and 2 Groups E, F, and G

Circuit is non-incendive when connected
per drawing 140979

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Class III

Enclosure Type 4

T5 @ Ta = -50° C to +40° C

T4 @ Ta = -50° C to +80° C

CA housings can only be ordered for North American End Users. For all other end user countries, housings 21000 and 24701 must be ordered.



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com