

Bently Nevada 330101-00-16-50-02-05

Manufacturer : Bently Nevada

Product No. : 330101-00-16-50-02-05

Product Type : 3300 XL 8 mm Probe, 3/8-24 UNF thread,
without armor

Made in U.S.A

330101 - 3300 XL 8 mm Probe, 3/8-24 UNF thread, without armor

Unthreaded Length Option : 00 - 0.0 in

Overall Case Length Option : 16 - 1.6 in

Total Length Option : 50 =5.0 meters (16.4 feet)

5-meter probes are designed for
use with the 5 meter Proximity
sensor only.

Connector and Cable-Type Option :02= Miniature coaxial ClickLoc
connector, standard cable

Agency Approval Option

05 =CSA, ATEX, IECEx Approvals

The 3300 XL probe and extension cable also reflect improvements over previous designs. A patented TipLoc molding method provides a more robust bond between the probe tip and the probe body. The probe's cable incorporates a patented CableLoc design that provides 330 N (75 lbf) pull strength to more securely attach the probe cable and probe tip.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

You can also order 3300 XL 8 mm probes and extension cables with an optional FluidLoc cable option. This option prevents oil and other liquids from leaking out of the machine through the cable's interior.

8 mm probes provide a thicker encapsulation of the probe coil in the molded PPS plastic probe tip. This results in a more rugged probe. The larger diameter of the probe body also provides a stronger, more robust case. We recommend that you use 8 mm probes when possible to provide optimal robustness against physical abuse

Nominal Probe DC Resistance
Resistance (RPROBE) from Center Conductor
to Outer Conductor
Probe
Length (m) 5.0
RPROBE(Ω)

8.73 $\pm$ 0.50

Extension Cable
Capacitance
69.9 pF/m (21.3 pF/ft)
typical
Field Wiring
0.2 to 1.5 mm² (16 to 24
AWG). Recommend using
3 conductor shielded triad
cable and tinned field
wiring. Maximum length of
305 meters (1,000 feet)
between the 3300 XL

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Proximity Sensor and the monitor. See the frequency response graphs, Figures 10 and 12, for signal rolloff at high frequencies when using longer field wiring lengths.

Linear Range

2 mm (80 mils). Linear range begins at approximately 0.25 mm (10 mils) from target and is from 0.25 to 2.3 mm (10 to 90 mils) (approximately -1 to -17 Vdc).

Recommended

Gap Setting for

Radial Vibration

-9 Vdc [approximately 1.27 mm (50 mils)]

Incremental Scale Factor (ISF)

Standard 5 or 1

meter System

7.87 V/mm (200 mV/mil) $\pm$ 5% including

interchangeability error

when measured in

increments of 0.25 mm (10 mils) over the 80 mil linear range from 0° C to +45° C (+32° F to +113° F).

Standard 9

meter System

7.87 V/mm (200 mV/mil)

$\pm$ 6.5% including

interchangeability error

when measured in

increments of 0.25 mm (10 mils) over the 80 mil linear range from 0° C to +45° C (+32° F to +113° F).

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Extended
Temperature
Range (ETR) for 5
and 9 Meter
Systems
7.87 V/mm (200 mV/mil) $\pm$
6.5% including
interchangeability error
when measured in
increments of 0.25 mm (10
mils) over the 80 mil linear
range from 0° C to +45° C
(+32° F to +113° F).
Deviation from best fit straight line (DSL)
Standard 5 or 1
meter System
Less than ± 0.025 mm (± 1
mil) with components at
0° C to +45° C (+32° F to
+113° F).
Standard 9
meter System
Less than ± 0.038 mm (± 1.5
mil) with components at
0° C to +45° C (+32° F to
+113° F).
Extended
Temperature
Range 5 and 9
meter Systems
Less than ± 0.038 mm (± 1.5
mil) with components at
0° C to +45° C (+32° F to
+113° F).

Probe Tip
Material Polyphenylene sulfide (PPS).
Probe Case
Material
AISI 303 or 304 stainless steel
(SST).

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

323 g/m (11.4 oz)

Probe Temperature Range

Operating and Storage Temperature

Standard

Probe

-52° C to +177° C (-62° F to

+350° F)

Extended

Temperature

Range Probe

-52° C to +218° C (-62° F to

+425° F) for the probe tip; -

51° C to +260° C (-60° F to

+500° F) for the probe cable

and connector.

Exposing the probe to temperatures

below - 34° C (-30° F) may cause

premature failure of the pressure

seal.



Probe Pressure

3300 XL 8 mm probes are designed to seal differential pressure between the probe tip and case. The probe sealing material consists of a Viton® O ring. Probes are not pressure tested prior to shipment. Contact our custom design department if you require a test of the pressure seal for your application.

Probe Relative Humidity

Less than a 3% change in Average Scale

Factor (ASF) when tested in 93% humidity in accordance with IEC standard 68 2 3 for up to

56 days.

Thread Engagement Limits

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Probe Case Thread 3/8-24
Maximum Length of Thread Engagement
0.563 in

Probe Case Torque
Probe Type Standard forward mounted probes

Maximum Rated 33.9 N•m (300 in•lbf)

Recommended 11.2 N•m (100 in•lbf)

Probe Case Torque
Probe Type Standard forward mount probes - first three threads

Maximum Rated 22.6 N•m (200 in•lbf)

Recommended 7.5 N•m (66 in•lbf)

Temperature Schedule
(Probe Only)

For EPL Ga and Gc

Temperature Classification T1 Ambient Temperature -55° C to +232° C

Temperature Classification T2 Ambient Temperature -55° C to +177° C

Temperature Classification T3 Ambient Temperature -55° C to +120° C

Temperature Classification T4 Ambient Temperature -55° C to +80° C

Temperature Classification T5 Ambient Temperature -55° C to +40° C

For EPL Dc

Temperature Classification T280° C @ Ta Ambient Temperature -55° C to +232° C

Temperature Classification T225° C @ Ta Ambient Temperature -55° C to +177° C

Temperature Classification T170° C @ Ta Ambient Temperature -55C to +120° C

Temperature Classification T130° C @ Ta Ambient Temperature -55° C to +80° C

Temperature Classification T105° C @ Ta Ambient Temperature -55° C to +100° C

Temperature Classification T90° C @ Ta Ambient Temperature -55° C to +40° C

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com