

FANUC A06B-6066-H008

The FANUC A06B-6066-H008 is an AC servo amplifier designed to control CNC systems precisely. It can control position, speed, and torque and serves as a single-axis drive application within a power supply range of 200 to 230 VAC.

Technical specifications for A06B-6066-H008

Manufacturer FANUC

Product Type AC Servo Amplifier (Servo Drive)

Product Line A06B

Part Number A06B-6066-H008

Weight 25.00 lbs (11.34 kg)

Control Type Position, Speed, and Torque Control

Axis 1 axis drive

Power Supply Single-phase

Application CNC Systems

Cooling Method Air Cooled

Input Voltage 200/220/230 VAC $\pm 10\%$ /-15%

Mounting Vertical/Wall-mounted

Frequency 50/60 Hz

Peak Current 240 A

Operating Temperature 0° C to 55° C

Protection Features Overload, Overcurrent, Overvoltage Protection

Rated Current 120 A

FANUC presents the A06B-6066-H008, a robust AC servo amplifier established for use in CNC systems. This servo drive excels in managing control aspects of positioning, speed, and torque, effectively supporting a one-axis maneuvering requirement. It operates using a single-phase power supply, accommodating input voltage fluctuations between 200 and 230 VAC and a tolerance of $\pm 10\%$ to -15%.

Designed for efficient cooling, the A06B-6066-H008 employs an air-cooled method, ensuring optimal thermal performance during operation. It is adaptable for installation, permitting vertical and wall-mounted configurations and allowing integration in varied setups. The device weighs 11.23 kg, striking a balance between durability and manageability.

This amplifier's operating frequency range is set to 50 or 60 Hz, making it versatile for a range of applications. Notably, this amplifier can handle peak currents up to 240 A while maintaining a rated current of 120 A, confirming its power handling characteristics. For environmental resilience, it operates efficiently in temperatures ranging from 0° C to 55° C.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Additionally, the A06B-6066-H008 encompasses protective features designed to safeguard the unit against potential hazards, including overload, overcurrent, and overvoltage conditions, ensuring longevity and reliability in extensive applications.



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com