

SICK CLV620-0120

CLV620-0120 | SICK Sensors | Fixed Mount Barcode Scanners

Features

Version Mid Range

Connection type Ethernet

Reading field Front

Sensor type Line scanner

Optical focus Fixed focus

Light source Light spot, laser, Visible, Red, 655 nm

Laser class 2, complies with 21 CFR 1040.10 except for the conformance according to “Laser Notice No.

56” from May 8, 2019 (EN 60825-1:2014+A11:2021, IEC 60825-1:2014)

Aperture angle $\leq 50^\circ$

Reading distance 60 mm ... 365 mm

Scanning frequency 400 Hz ... 1,200 Hz

Code resolution 0.2 mm ... 1 mm

Mechanics/electronics

Connection type 2 x M12 cylindrical connectors (12-pin male connector, 4-pin female connector) on swivel connector

Supply voltage 10 V DC ... 30 V DC

Power consumption 4.5 W

Housing material Aluminum die cast

Housing color Light blue (RAL 5012)

Window material Glass

Enclosure rating IP65 (DIN 40 050)

Protection class III (VDE 0106/IEC 1010-1)

Weight 205 g, without connecting cable

Dimensions (L x W x H) 61 mm x 66 mm x 38 mm

MTBF 100,000 h

MTTF 40,000 h (Laser diode)

Performance

Readable code structures 1D codes

Bar code types All current code types, Code 39, Code 128, Code 93, Codabar, GS1-128 / EAN 128, UPC /

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

GTIN / EAN, Interleaved 2 of 5, Pharmacode, GS1 DataBar, Telepen, MSI/Plessey

Code printing process Label (printed codes)

Print ratio 2:1 ... 3:1

No. of codes per scan 1 ... 20 (Standard decoder)

1 ... 6 (SMART620)

No. of codes per reading interval 1 ... 50 (auto-discriminating)

No. of characters per reading interval 1,500

500 (for multiplexer function in CAN operation)

No. of multiple readings 1 ... 99

Interfaces

Ethernet ✓ , TCP/IP

Function Data interface (read result output), Service interface

Data transmission rate 10/100 MBit/s

PROFINET ✓

Function PROFINET Single Port, PROFINET Dual Port (optional via external connection module CDF600-2)

Data transmission rate 10/100 MBit/s

EtherNet/IP™ ✓

Data transmission rate 10/100 MBit/s

EtherCAT® ✓

Type of fieldbus integration Optional over external fieldbus module CDF600

Serial ✓ , RS-232, RS-422, RS-485

Function Data interface (read result output), Service interface

Data transmission rate 2,400 Baud ... 115.2 kBaud, AUX: 57.6 kBaud (RS-232)

CAN ✓

Function SICK CAN sensor network CSN (CAN controller/CAN device, multiplexer/server)

Data transmission rate 20 kbit/s ... 1 Mbit/s

CANopen ✓

Data transmission rate 20 kbit/s ... 1 Mbit/s

PROFIBUS DP ✓

Type of fieldbus integration Optional over external fieldbus module CDF600-2

Digital inputs 3 (“ Sensor 1 ” , 2 inputs via optional parameter storage CMC600 in CDB620/CDM420)

Digital outputs 2 (Via optional CMC600 parameter memory in CDB620/CDM420)

Reading pulse Digital inputs, non-powered, serial interface, auto pulse, CAN

Optical indicators 6 LEDs (Ready, Result, laser, Data, CAN, LNK TX)

Acoustic indicators Beeper/buzzer (can be switched off, can be allocated as a result indication function)

Configuration software SOPAS ET

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Ambient data

Electromagnetic compatibility (EMC) EN 61000-6-3 (2001-10) / EN 61000-6-2:2005

Vibration resistance EN 60068-2-6 (1995)

Shock resistance EN 60068-2-27 (1993)

Ambient operating temperature 0 ° C ... +40 ° C

Storage temperature - 20 ° C ... +70 ° C

Permissible relative humidity 90 %, Non-condensing

Ambient light immunity 2,000 lx, on barcode

Bar code print contrast (PCS) $\geq$ 60 %



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com