

SICK S30A-6011GB

Product Model: S30A-6011GB

Product Brand: SICK

Product Series: S3000

=== General Identification ===

- Part Number: 1052108
- Product Sub-Series / Family: S3000 Expert (Medium Range)
- Measurement Principle: 2D LiDAR Optoelectronic Pulsed Laser Safety Scanning (Time-of-Flight)

=== Technical & Optical Parameters ===

- Measuring / Protective Range: Protective field range: 5.5 m; Warning field range: 49 m radial warning field
- Light Source: Pulsed laser diode (wavelength 905 nm; Class 1 eye-safe per IEC 60825-1:2014; average optical power < 1 mW)
- Laser Class: Class 1 (IEC 60825-1:2014, EN 60825-1:2014, Eye-safe)
- Response Time: ≤ 60 ms (Configurable via multiple sampling rate: 60 ms ... 120 ms)
- Scanning Angle: 190° scanning angle (0.25° or 0.5° angular resolution)
- Object Resolution: 30 mm / 40 mm / 50 mm / 70 mm / 150 mm (Configurable depending on resolution setup)
- Safety Integrity Level: Type 3 (IEC 61496-1, -3), SIL 2 (IEC 61508), SILCL 2 (EN 62061), PL d / Category 3 (EN ISO 13849-1)
- Measurement Accuracy: Systematic measurement error: Typ. ± 35 mm

=== Interface & Electrical Specifications ===

- Output & Communication Interface: Safety Outputs: 1x OSSD pair (PNP, 250 mA); Incremental encoder inputs; CMS raw contour data output; Safe EFI bus
- Supply Voltage: DC 24 V (16.8 V ... 28.8 V; SELV/PELV safety extra-low voltage)
- Power Consumption: Typ. 19 W (Without external output loads)
- Electrical Connection: System plug with comprehensive I/O interfaces

=== Mechanical & Environmental Specifications ===

- Ambient Temperature, Operation: -10 ° C ... +50 ° C
- Ambient Temperature, Storage: -20 ° C ... +70 ° C
- Enclosure Protection Rating: IP65 (EN 60529)
- Physical Dimensions (W x H x D): 155 mm x 185 mm x 160 mm
- Housing Material: Aluminum die-cast with polycarbonate (PC) optical hood
- Device Weight: Approx. 3.3 kg

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

=== Features & Functional Highlights ===

- Maximum safeguarding flexibility with 5.5 m protective field: Up to 32 monitoring cases and 64 fields
- Triple-field mode (1 protective, 2 warning fields) for staged machine slowing and stopping
- Simultaneous CMS contour measurement output and velocity-dependent safety monitoring



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com