

Schneider Electric BMXDDM3202K

Model: BMXDDM3202K

Brand: Schneider Electric

Series: Modicon X80

Modicon X80 Mixed Discrete I/O Module, 32-channel (16DI + 16DO), High Density

—— I/O Specifications ——

Channels: 32 channels (16 DI + 16 DO)

Signal type: DI: 24V DC; DO: transistor 24V DC

Range: DI: 24 V DC; DO: 24 V DC

Resolution: Not applicable (discrete)

Accuracy: Not applicable (discrete)

Isolation: Group-to-group isolation

Diagnostics: Module status LED

Connection: 40-pin terminal block (high density)

—— Electrical ——

Supply voltage: 24 V DC

Power consumption: 4.3 W

Bus current: 180 mA @ 24 V DC

—— Environmental ——

Operating temperature: 0° C to +60° C

Storage temperature: -25° C to +70° C

Relative humidity: 5% to 95% (non-condensing)

Protection rating: IP20

—— Physical ——

Dimensions (H×W×D): 100 × 28 × 93 mm

Weight: 0.18 kg

—— Lifecycle ——

Lifecycle: Active (shared I/O platform for M340 and M580) (Last verified: 2026-09)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com