

Schneider Electric BMXDDO3202K

Model: BMXDDO3202K

Brand: Schneider Electric

Series: Modicon X80

Modicon X80 Discrete Output Module, 32-channel, 24V DC Transistor, High Density

— I/O Specifications —

Channels: 32 channels

Signal type: Transistor output

Range: 12/24 V DC, 0.55 A per channel (17.6 A module max)

Resolution: Not applicable (discrete)

Accuracy: Not applicable (discrete)

Isolation: Group-to-group isolation

Diagnostics: Module status LED

Response time: 0.3 ms

Parallel: up to 3 channels

MTBF: 833,000 h

Connection: 40-pin terminal block (high density)

— Electrical —

Supply voltage: 12/24 V DC (field)

Power consumption: 3.1 W

Bus current: 130 mA @ 24 V DC

— Environmental —

Operating temperature: 0° C to +60° C

Storage temperature: -25° C to +70° C

Relative humidity: 5% to 95% (non-condensing)

Protection rating: IP20

— Physical —

Dimensions (H×W×D): 100 × 28 × 93 mm

Weight: 0.142 kg

— Lifecycle —

Lifecycle: Active (shared I/O platform for M340 and M580) (Last verified: 2026-09)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com