

Schneider Electric TM3AM6G

Model: TM3AM6G

Brand: Schneider Electric

Series: Modicon TM3

Analog Mixed Module, 4 inputs + 2 outputs, 12-bit, spring terminals

—— I/O Specifications ——

Module type: Analog mixed (4 AI + 2 AO)

Channels: 4 analog inputs + 2 analog outputs

Signal type (inputs): 0-10 Vdc, ± 10 Vdc, 0-20 mA, 4-20 mA (configurable per channel)

Signal type (outputs): 0-10 Vdc, ± 10 Vdc, 0-20 mA, 4-20 mA (configurable per channel)

Range: 0-10 V / ± 10 V / 0-20 mA / 4-20 mA

Resolution: 12 bits (AI and AO)

Accuracy: $\pm 0.1\%$ of full scale at 25 ° C ($\pm 1\%$ FS over temperature)

Isolation: 1500 V AC between analog I/O and supply; 500 V AC between analog I/O and internal logic

Diagnostics: Channel status, module status, bus status

Response time: Conversion: 1 ms + 1 ms per channel + 1 controller cycle time

Wiring: Removable spring-cage terminal block, 3.81 mm pitch

—— Electrical ——

Supply voltage: 24 Vdc (via TM3 bus)

Power consumption: Not available

Bus current: 50 mA at 5 V DC (full load); 50 mA at 24 V DC (full load)

—— Environmental ——

Operating temperature: 0...+55 ° C

Storage temperature: -25...+70 ° C

Protection rating: IP20

—— Physical ——

Dimensions (H × W × D): 90 × 23.6 × 70 mm

Weight: 0.11 kg

—— Compatibility ——

Compatible platforms: Modicon M221, M241, M251, M262

—— Status ——

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Lifecycle: Active (Last verified: 2026-09)

—— Lifecycle ——

Active (Modicon TM3 expansion modules for M2xx/M340 PLCs)



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com