

Schneider Electric TM3AQ4

Model: TM3AQ4

Brand: Schneider Electric

Series: Modicon TM3

Analog Output Module, 4 channels, 12-bit

— I/O Specifications —

Module type: Analog output (voltage/current configurable per channel)

Channels: 4

Signal type: 0-10 Vdc, ± 10 Vdc, 0-20 mA, 4-20 mA (software configurable per channel)

Range: 0-10 V / ± 10 V / 0-20 mA / 4-20 mA

Resolution: 12 bits

Accuracy: $\pm 0.2\%$ of full scale at 25 ° C ($\pm 1\%$ FS over temperature)

Isolation: 1500 V AC between output and supply; 500 V AC between output and internal logic

Diagnostics: Module status, bus status

Response time: Conversion: 1 ms + 1 ms per channel + 1 controller cycle time; stabilization 1 ms

Wiring: Removable screw terminal block, 5.08 mm pitch

— Electrical —

Supply voltage: 24 Vdc (via TM3 bus)

Power consumption: Not available

Bus current: 50 mA at 5 V DC (full load); 80 mA at 24 V DC (full load)

— Environmental —

Operating temperature: 0...+55 ° C

Storage temperature: -25...+70 ° C

Protection rating: IP20

— Physical —

Dimensions (H × W × D): 90 × 23.6 × 70 mm

Weight: 0.115 kg

— Compatibility —

Compatible platforms: Modicon M221, M241, M251, M262

— Status —

Lifecycle: Active (Last verified: 2026-09)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

—— Lifecycle ——

Active (Modicon TM3 expansion modules for M2xx/M340 PLCs)



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com