

Schneider Electric TM3DQ16TG

Model: TM3DQ16TG

Brand: Schneider Electric

Series: Modicon TM3

Digital Output Module, 16 channels, transistor 0.5 A, spring terminals

—— I/O Specifications ——

Module type: Digital output (transistor, source/PNP)

Channels: 16

Signal type: 24 Vdc transistor output, source (PNP)

Range: 24 Vdc (nominal)

Output current: 0.5 A per channel (max)

Resolution: N/A

Accuracy: N/A

Isolation: 500 V AC between output and internal logic; no isolation between channels

Diagnostics: Module status, bus status; short-circuit and overload protection

Response time: 450 μ s max. (turn on/off)

Wiring: Removable spring-cage terminal block, 3.81 mm pitch

—— Electrical ——

Supply voltage: 24 Vdc (via TM3 bus)

Power consumption: Not available

Bus current: 35 mA at 5 V DC (all outputs on); 5 mA (all outputs off)

—— Environmental ——

Operating temperature: 0...+55 ° C

Storage temperature: -25...+70 ° C

Protection rating: IP20

—— Physical ——

Dimensions (H × W × D): 90 × 27.4 × 84.6 mm

Weight: 0.11 kg

—— Compatibility ——

Compatible platforms: Modicon M221, M241, M251, M262

—— Status ——

Lifecycle: Active (Last verified: 2026-09)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

—— Lifecycle ——

Active (Modicon TM3 expansion modules for M2xx/M340 PLCs)



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com