

Keyence GT-76A

Model: GT-75A

Brand: Keyence

Series: GT series

General purpose digital contact sensor amplifier unit, Panel mount, NPN output, main unit.

—— Hardware ——

Type: Digital contact sensor amplifier unit

Mounting: Panel mount, Main unit

Display range: -99.999 to 999.999

Display resolution: 1 μ m

Sampling rate: 2,000 times/second

Response time: hsp (1.5 ms), 5 ms, 10 ms, 100 ms, 500 ms, 1 s, 5 s (selectable)

—— Communication ——

Built-in ports: None

Protocols: None

Communication expansion: Via optional GT series communication units (sold separately)

—— Electrical ——

Supply voltage: 12 to 24 VDC, ripple (p-p) 10 % or less

Power consumption: Normal 1,140 mW (95 mA) or less at 12 V / 1,200 mW (50 mA) or less at 24 V; power-saving (Eco) 600 mW (50 mA) or less at 12 V / 840 mW (35 mA) or less at 24 V

Output type: HIGH/GO/LOW NPN open collector, max. 50 mA (40 V or less), residual voltage 1 V or less, N.O./N.C. selectable

—— Environmental ——

Operating temperature: -10 to +55 ° C (No freezing)

Storage temperature: Not available

Relative humidity: 35 to 85 % RH (No condensation)

Protection rating: Not available

—— Physical ——

Dimensions (H × W × D): Not available

Weight: Approx. 110 g (including power cable)

—— Lifecycle ——

Active; official Keyence production status confirmed via product/spec page (Last verified:

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

2026-09)



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com