

Keyence GT2-A12

Model: GT2-A12

Brand: Keyence

Series: GT2 series

High-accuracy digital contact sensor head, air push type, standard, 12 mm stroke.

—— Hardware ——

Detection system: Scale Shot System, absolute (no tracking error) type

Measuring range: 12 mm

Resolution: 0.5 μm

Indicated accuracy: 2 μm (p-p)

Measuring force (downward mounting): 1.2 N

Measuring force (side mounting): 1.1 N

Measuring force (upward mounting): 1.0 N

Sampling cycle: 1 ms

Mechanical response: Not available

Operation indicator: 2-colour LED (red, green)

Fluid used: Dry air

Pressure resistance: 1 MPa

Applied pressure range: 0.25 to 0.50 MPa

—— Communication ——

Built-in ports: None

Protocols: None

Communication expansion: None

—— Electrical ——

Supply voltage: Not available (powered by GT2 series amplifier)

Power consumption: Not available

Output type: Not available (sensor head; connects to GT2 amplifier via M8 connector)

—— Environmental ——

Operating temperature: 0 to +55 °C (No freezing)

Storage temperature: Not available

Relative humidity: 35 to 85 % RH (No condensation)

Protection rating: IP67 (IEC)

—— Physical ——

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Dimensions (H×W×D): Not available

Weight: Approx. 145 g (not including cable)

—— Lifecycle ——

Active; official Keyence production status confirmed via product/spec page (Last verified: 2026-09)



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com