Keyence　IL-065

Model: IL-065
Brand: Keyence
Series: IL series

CMOS laser displacement sensor head, mid-range reflective type.

—— Hardware ——
Sensor type: CMOS laser displacement sensor head (triangulation, reflective)
Reference distance: 65 mm
Measurement range: 55 to 105 mm
Light source: Red semiconductor laser, wavelength 655 nm (visible light)
Laser output: 560 µW
Laser class: Class 2 (IEC 60825-1; FDA CDRH Part1040.10)
Spot diameter (at standard distance): Approx. 550 x 1,750 µm
Linearity: ±0.1 % of F.S. (55 to 75 mm)
Repeatability: 2 µm (standard white diffuse target, 1 ms sampling)
Sampling rate: 0.33 / 1 / 2 / 5 ms (4 levels selectable)
Temperature characteristics: 0.06 % of F.S./° C

—— Communication ——
Built-in ports: None
Protocols: None
Communication expansion: None

—— Electrical ——
Supply voltage: Not available (powered by IL series amplifier unit)
Power consumption: Not available
Output type: Not available (sensor head; connects to IL amplifier)

—— Environmental ——
Operating temperature: -10 to +50 ° C (No condensation or freezing)
Storage temperature: Not available
Relative humidity: 35 to 85 % RH (No condensation)
Protection rating: IP67

—— Physical ——
Dimensions (H×W×D): Not available
Weight: Approx. 75 g

You can contact us through the following contact information

www.sparetechplc.com　+86 180 3000 5825　sales@sparetechplc.com

—— Lifecycle ——

Active; official Keyence production status confirmed via product/spec page (Last verified: 2026-09)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com