

## Yokogawa F3XA08-1N

### YOKOGAWA F3XA08-1N AC INPUT

Input type: AC voltage

Number of inputs: 8

Isolation method: Photocoupler isolation

Rated input voltage: 100 – 120 V AC 50/60 Hz

Rated input current: 5.4 - 6.5 mA/point 100-120V AC,60Hz

Operating voltage range: 85-132 V AC 50/60Hz

Operating voltage/current — ON: 80 V AC min. 5 mA min.

Operating voltage/current — OFF: 40 V AC max. 1 mA max.

Input response time — OFF→ON: Selectable from 15 ms max. or 30 ms

Input response time — ON→OFF: Selectable from 25 ms max. or 40 ms

Maximum ratio of inputs turned on simultaneously: 100%

External connection: 10-point terminal block M3.5 screw

Common points: 8 points/common

Interrupt \*2: Can be specified for each input point.

Current consumption: 40mA (5V DC)

Weight: 130 g

Model and suffix codes: F3XA08 -1N . . . . . — 100-120 V AC input, 8 points

Surrounding air temperature range: Operating: 0 to 55° C / Storage: -20° C to 75° C

Surrounding humidity range: Operating: 10 to 90% RH (non-condensing) / Storage: 10 to 90% RH (non-condensing)

Surrounding atmosphere: Must be free of corrosive gases, flammable gases or heavy dust.

You can contact us through the following contact information

[www.sparetechplc.com](http://www.sparetechplc.com) +86 180 3000 5825 [sales@sparetechplc.com](mailto:sales@sparetechplc.com)