Yokogawa F3XA08-2N

Yokogawa input module F3XA08-2N
Input type: AC voltage
Number of inputs: 8
Isolation method: Photocoupler isolation
Rated input voltage: 200 – 240 V AC 50/60 Hz
Rated input current: 5.1 - 6.1 mA/point 200-240 V AC,60Hz
Operating voltage range: 170-264 V AC 50/60Hz
Operating voltage/current — ON: 160 V AC min. 4 mA min.
Operating voltage/current — OFF: 70 V AC max. 1 mA max.
Input response time — OFF→ON: Selectable from 15 ms max. or 30 ms
Input response time — ON→OFF: Selectable from 25 ms max. or 40 ms
Maximum ratio of inputs turned on simultaneously: 100%
External connection: 10-point terminal block M3.5 screw
Common points: 8 points/common
Interrupt *2: Can be specified for each input point.
Current consumption: 40mA (5V DC)
Weight: 130 g
Model and suffix codes: F3XA08 -2N . . . . . — 200-240 V AC input, 8 points
Surrounding air temperature range: Operating: 0 to 55° C / Storage: -20° C to 75° C
Surrounding humidity range: Operating: 10 to 90% RH (non-condensing) / Storage: 10 to 90% RH (non-condensing)
Surrounding atmosphere: Must be free of corrosive gases, flammable gases or heavy dust.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com