Yokogawa F3XD64-3F

Yokogawa F3XD64-3F DC Input Module
Input type: DC voltage (sink/source)
Number of inputs: 64
Isolation method: Photocoupler isolation
Rated input voltage: 24V DC
Rated input current: 4.1 mA/point 24 V DC
Operating voltage range: 20.4 - 26.4 V DC
Operating voltage/current — ON: 16.0 V DC min. 3.2 mA min.
Operating voltage/current — OFF: 5.8 V DC max. 0.9 mA max.
Input response time — OFF→ON: Input sampling time can be specified for 4 steps: Always (0 μs), 62.5 μs, 250 μs and 1ms. *1*2
Input response time — ON→OFF: Input sampling time can be specified for 4 steps: Always (0 μs), 62.5 μs, 250 μs and 1ms. *1*2
Maximum ratio of inputs turned on simultaneously: 60%
External connection: Two 40-pin connectors
Common points: 8 points/common
Interrupt: None
Current consumption: 100mA (5V DC)
Weight: 160 g
Model and suffix codes: F3XD64 -3F . . . . . — DC input sink/source, 24 V DC, 64 points*
Surrounding air temperature range: Operating: 0 to 55° C / Storage: -20° C to 75° C
Surrounding humidity range: Operating: 10 to 90% RH (non-condensing) / Storage: 10 to 90% RH (non-condensing)
Surrounding atmosphere: Must be free of corrosive gases, flammable gases or heavy dust.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com