

Yokogawa F3XD64-4F

Yokogawa F3XD64-4F DC Input Module

Input type: DC voltage (sink/source)

Number of inputs: 64

Isolation method: Photocoupler isolation

Rated input voltage: 12 V DC

Rated input current: 4.1 mA/point 12 V DC

Operating voltage range: 10.2 - 13.2 V DC

Operating voltage/current — ON: 8.0 V DC min. 2.6 mA min.

Operating voltage/current — OFF: 3.4 V DC max. 1.0 mA max.

Input response time — OFF→ON: Input sampling time can be specified for 4 steps: Always (0 μ s), 62.5 μ s, 250 μ s and 1ms. *1*2

Input response time — ON→OFF: Input sampling time can be specified for 4 steps: Always (0 μ s), 62.5 μ s, 250 μ s and 1ms. *1*2

Maximum ratio of inputs turned on simultaneously: 60%

External connection: Two 40-pin connectors

Common points: 8 points/common

Interrupt: None

Current consumption: 100mA (5V DC)

Weight: 160 g

Model and suffix codes: F3XD64 -4F — DC input sink/source, 12 V DC, 64 points*

Surrounding air temperature range: Operating: 0 to 55° C / Storage: -20° C to 75° C

Surrounding humidity range: Operating: 10 to 90% RH (non-condensing) / Storage: 10 to 90% RH (non-condensing)

Surrounding atmosphere: Must be free of corrosive gases, flammable gases or heavy dust.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com