

Yokogawa F3YA08-2N

YOKOGAWA F3YA08-2N Output type: TRIAC contact

Number of outputs: 8

Points/common: 8 points/common

Isolation method: Photocoupler Isolation

Rated load voltage: 100—240 V AC

Maximum load current: 1 A/point (0 - 40° C) 0.7 A/point (40 - 55° C) 3 A/common

Response time — OFF→ON: 1 ms max.

Response time — ON→OFF: 1/2 cycle +1 ms max.

Life: —

ON voltage: 1.5 V AC max.

Off-time leakage current: 3 mA max.

Surge protector: CR absorber Varistor

CPU error output *2 HOLD/RESET: Not required

Current consumption: 130 mA (5 V DC)

External power supply: Not required

External connection: 10-point terminal block M3.5 screw

Weight: 150 g

Model and suffix codes: F3YA08 -2N — TRIAC output, 100—240 V AC 1 A, 8 points

Surrounding air temperature range: Operating: 0 to 55° C / Storage: -20° C to 75° C

Surrounding humidity range: Operating: 10 to 90% RH (non-condensing) / Storage: 10 to 90% RH (non-condensing)

Surrounding atmosphere: Must be free of corrosive gases, flammable gases or heavy dust.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com