

Yokogawa F3YD32-1T

YOKOGAWA F3YD32-1T Output type: Transistor contact (TTL output)

Number of outputs: 32

Points/common: 8 points/common

Isolation method: Photocoupler Isolation

Rated load voltage: 5 V DC

Maximum load current: 16 mA/point 128 mA/common

Response time — OFF→ON: 1 ms max.

Response time — ON→OFF: 1 ms max.

Life: —

ON voltage: —

Off-time leakage current: —

Surge protector: Zener diode

CPU error output *2 HOLD/RESET: When a sequence CPU is used: Initial value: RESET. When a BASIC CPU is used: No setting function; always set to HOLD. When an OS-free CPU is used: Initial value: HOLD; can be specified for each set of 8 points. All module outputs can be set collectively *1.

Current consumption: 210 mA (5 V DC)

External power supply: 5 V DC 60 mA

External connection: One 40-pin connector

Weight: 110 g

Model and suffix codes: F3YD32 -1T — TTL output, 5 V DC, 32 points*

Surrounding air temperature range: Operating: 0 to 55° C / Storage: -20° C to 75° C

Surrounding humidity range: Operating: 10 to 90% RH (non-condensing) / Storage: 10 to 90% RH (non-condensing)

Surrounding atmosphere: Must be free of corrosive gases, flammable gases or heavy dust.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com