

Yokogawa F3YD64-1M

YOKOGAWA F3YD64-1M Output type: Transistor contact (matrix scan)

Number of outputs: 64

Points/common: 8 x 8 matrix

Isolation method: Photocoupler Isolation

Rated load voltage: 12 — 24 V DC

Maximum load current: 0.1 A

Response time — OFF→ON: 16 ms max.

Response time — ON→OFF: 16 ms max.

Life: —

ON voltage: 1.5 V DC max.

Off-time leakage current: 0.1 mA max.

Surge protector: Zener diode

CPU error output *2 HOLD/RESET: When a sequence CPU is used: Initial value: RESET. When a BASIC CPU is used: No setting function; always set to HOLD. When an OS-free CPU is used: Initial value: HOLD; can be specified for each set of 8 points. All module outputs can be set collectively *1.

Current consumption: 125 mA (5 V DC)

External power supply: 12 — 24 V DC 40 mA

External connection: One 40-pin connector

Weight: 110 g

Model and suffix codes: F3YD64 -1M — Transistor output (matrix scan), 12 — 24 V DC 0.1 A, 64 points

Surrounding air temperature range: Operating: 0 to 55° C / Storage: -20° C to 75° C

Surrounding humidity range: Operating: 10 to 90% RH (non-condensing) / Storage: 10 to 90% RH (non-condensing)

Surrounding atmosphere: Must be free of corrosive gases, flammable gases or heavy dust.

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com