

Yokogawa F3YD64-1P

Output type: Transistor contact (sink type)

Number of points: 64

Common line type: 8 points/common

Isolation method: Photocoupler isolation

Withstanding voltage: 1500 V AC for one minute between the group of terminals for external connection and the internal circuit

Rated load voltage (Operating voltage range): 12 to 24 V DC (10.2 to 26.4 V DC)

Maximum load current: 0.1 A/point 0.4 A/common

Response time — OFF→ON: 1 ms max.

Response time — ON→OFF: 1 ms max.

ON voltage: 0.5 V DC max.

Off-time leak current: 0.1 mA max.

Service life — Mechanical: —

Protectors *1 — Short-circuit: Limit the output current or output shutdown

Protectors *1 — Overheat: Output shutdown

Surge Protector *2: Active clamp circuit

Fuse: None

Current consumption: 275 mA (5 V DC)

Output display *3: LED (Lit when outputs are turned on for a switched LED group)

Output status when program stops *4 HOLD/RESET: When a sequence CPU is used: Initial value: RESET, Can be set globally on a module-by-module basis *5. When a BASIC CPU is used: No setting function; The status is always HOLD. When an OS-free CPU is used: Initial value: HOLD, Can be specified for each set of 8 points.

External power supply: 12 to 24 V DC 95 mA

External connection: Two 40-pin connectors

Weight: 130 g

Operating environment: This module is compatible with all CPU module types.

Model and suffix codes: F3YD64 -1P — 64-point transistor output with short-circuit protector

Note *1 (protection circuitry): If short-circuit occurs, the output current is limited or the output is turned off for a certain period of time. If the short-circuit condition is removed, normal operation resumes. If the short-circuit condition persists, the temperature of the output element will rise. When the internal temperature of the output element exceeds a certain temperature, overheat protection is activated and the output is turned off. Short-circuit protectors control outputs individually. Overheat protectors control outputs in 8 units (OUT1-OUT8, OUT9-OUT16, ... OUT57-OUT64).

Surrounding air temperature range: Operating: 0 to 55° C / Storage: -20° C to 75° C

Surrounding humidity range: Operating: 10 to 90% RH (non-condensing) / Storage: 10 to 90% RH

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

(non-condensing)

Surrounding atmosphere: Must be free of corrosive gases, flammable gases or heavy dust.



You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com