Allen-Bradley 1606-XLE240E-3

Model: 1606-XLE240E-3
Brand: Allen-Bradley
Series: Bulletin 1606-XL

1606-XLE Essential switched-mode power supply, 24 V DC output, 240 W, three-phase AC input.

—— Hardware ——
Mounting: DIN rail and wall mounting
Output: 24 V DC nominal, adjustable 24…28 V DC
Output current: 10 A maximum (240 W)
DC OK relay contact: present
Connection: screw terminals
Protection: dynamic 120 % power boost up to +45 ° C

Approvals: UL 60950-1 / cUL / CE marked (per official Bulletin 1606 series standard)
—— Communication ——
Built-in ports: None (no communication interface; DC OK relay signal contact only)
Protocols: None (no communication interface)

—— Electrical ——
Input voltage: 380…480 V AC, 3-phase nominal
Output voltage: 24 V DC nominal, adjustable 24…28 V DC
Output current: 10 A maximum
Rated power: 240 W
Efficiency: 92.8 % typical

—— Environmental ——
Operating temperature: -25 to +70 ° C
Storage temperature: -25 ° C (lower bound published; full range not published numerically on product page)
Relative humidity: 5 to 95 %
Protection rating: IP20

—— Physical ——
Dimensions (H × W × D): 124 × 62 × 117 mm (unit body)
Weight: 0.75 kg

—— Lifecycle ——

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

Current: Active on official Rockwell product page (Last verified: 2026-10)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com