Honeywell 2MLI-CPUH

Max. I/O: 6,144Pts, 3.5MB Program Memory, IEC, High Perf.
PROGRAMMABLE LOGIC CONTROLLER
512K BYTE
6144 POINTS MAX
3.5 MB
IEC
0-55 DEGREES C
MASTERLOGIC 200 SERIES
Manufacturer : Honeywell

Part Number : 2MLI-CPUH

MasterLogic-200 Series

Operation system : Reiterative operation, fixed cycle operation, constant scan

I/O Control system : Scan synchronous batch processing system(refresh system), direct system by command

Program language : Ladder Diagram, SFC (Sequential Function Chart), ST(Structure Text)

Operator : 18

Basic function : 136 types + real number operation function

Basic function block : 43

Dedicated function block : Dedicated function blocks by special function

modules, communication

dedicated function block(P2P)

Basic : 0.028 ? / step

MOVE : 0.084? / step

Program memory capacity : 3.5 MB

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com

I/O points(installable) : 6,144 points

Max. I/O memory contact : 131,072 points

Symbolic variable area(A) : 512KB (max. 256KB retain settable)

I variable(I) : 16KB

O variable(Q) : 16KB

Direct variable : M : 256KB (max. 128KB retain settable)

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com