Honeywell 2MLR-AC12

2MLR-AC12 | Honeywell MasterLogic-200 | Power Supply Modules

Manufacturer : Honeywell

Prodcut Number : 2MLR-AC12

Rated input voltage: 110 VAC

Input frequency : 50 / 60 Hz (47 ~ 63 Hz)
Input voltage range:18 to 30 VDC

Rated input voltage 110 VAC
Input voltage range 85V~132VAC
Input frequency 50 / 60 Hz (47 ~ 63 Hz)
Max. input power 110 VA / 42 W
Inrush current 20A peak and lower (within8 ms)
Efficiency 65% or higher
Input fuse Built in(not replaceable by a user) - AC power:250V/3.15A(Time-lag Type)UL approved - DC power:125V/10A (Time-lag type) UL approved
Allowed instantaneous interruption Within 20 ms
Output voltage 5VDC (±2%)
Output current 5.5A
Output power 27.5W @ 55℃
Over current protection 6.0A~13.0A
Purpose RUN contact
Rated switching voltage/current 24VDC,0.5A
Min.switching load 5VDC,1 mA
Response time Off→On/ On→Off:10 ms and lower/12 ms and lower
Life Mechanical life:20million and more times, electrical life: rated switching current: 100 thousand and more times
Voltage status display LED On when output voltage is normal
Specification of cable 0.75~2mm^2
Available clamped terminal RAV1.25-3.5.RAV2-3.5
Dimension (W xH x D mm) 55 x 95x 90
Weight 326g

You can contact us through the following contact information

www.sparetechplc.com +86 180 3000 5825 sales@sparetechplc.com